



Ftool

Tutorial for the creation of a bridge model with static loads and live load trains, and visualization of results

Version 4.01

June 2024

<http://www.ftool.com.br>

This tutorial:

<https://www.tecgraf.puc-rio.br/ftool/downloads/tutorialloadtrain.zip>







Table of Contents


Create a file for the bridge model (command "Save as... ")	3
Specification of units and number formatting.....	3
Insertion of bridge beam in keyboard mode	4
Cancel member insertion to fit model image on screen	4
Fit image of model on screen.....	5
Insertion of first bridge column in keyboard mode.....	5
Insertion of second bridge column in keyboard mode	6
Insertion of third bridge column in keyboard mode.....	6
Insertion of fourth bridge column in keyboard mode.....	7
Cancel insertion of members	7
Leave keyboard mode and select area for zooming in	8
Mouse clicks for insertion of dimension line at bridge central span	8
Dimension line at bridge central span.....	9
Insertion of other dimension lines.....	9
Turn off display of dimension lines to simplify image	10
Creation of new material.....	10
Selection of material type and name; and assignment to all members	11
Creation of cross-section for bridge columns	11
Select rectangular cross-section for the bridge columns	12
Specify rectangular cross-section parameters and apply to bridge columns	12
Creation of cross-section for bridge beam members.....	13
Select type and name of cross-section for bridge beam members.....	13
Specify cross-section parameters and apply to bridge beam members	14
Definition of fixed support and assignment to inferior nodes	14
Definition of simple support and assignment to beam end nodes	15
Creation of uniformly distributed load (dead load) for bridge beam.....	15
Definition of dead load value and assignment to beam members	16
Select small display size for supports	16
Select small display size for loads	17
Specification of two vehicle live loads (load-trains).....	17
Creation of highway load-train with four axes.....	18
Specification of highway load-train length, values of concentrated forces, and values of interior and exterior live loads (population of small vehicles).....	18
Creation of railroad load-train	19
Specification of railroad load-train length, values of concentrated forces, and values of full and empty car distributed loads	19
Select result visualization step (2 m) and set transversal display of result values.....	20
Select cross-section for visualization of shear force influence line result	20
Visualization of shear force influence line result and critical positions (that cause minimum and maximum) of highway load-train.....	21
Visualization of bending moment influence line result and critical positions (that cause minimum and maximum) of highway load-train.....	21
Visualization of axial force influence line result and critical positions (that cause minimum and maximum) of railroad load-train.....	22
Visualization of shear force envelopes for highway load-train (including effect of permanent load).....	22
Visualization of bending moment envelopes for railroad load-train (including effect of permanent load).....	23
Visualization of bending moment envelopes for railroad load-train (excluding effect of permanent load)	23
Consulting step results values along central beam member of bending moment envelopes for railroad load-train (excluding effect of permanent load).....	24



Create a file for the bridge model (command "Save as... ")




Specification of units and number formatting






Insertion of bridge beam in keyboard mode




Cancel member insertion to fit model image on screen






Fit image of model on screen




Insertion of first bridge column in keyboard mode






Insertion of second bridge column in keyboard mode




Insertion of third bridge column in keyboard mode






Insertion of fourth bridge column in keyboard mode




Cancel insertion of members






Leave keyboard mode and select area for zooming in




Mouse clicks for insertion of dimension line at bridge central span






Dimension line at bridge central span




Insertion of other dimension lines






Turn off display of dimension lines to simplify image




Creation of new material






Selection of material type and name; and assignment to all members




Creation of cross-section for bridge columns






Select rectangular cross-section for the bridge columns




Specify rectangular cross-section parameters and apply to bridge columns






Creation of cross-section for bridge beam members




Select type and name of cross-section for bridge beam members






Specify cross-section parameters and apply to bridge beam members




Definition of fixed support and assignment to inferior nodes






Definition of simple support and assignment to beam end nodes




Creation of uniformly distributed load (dead load) for bridge beam






Definition of dead load value and assignment to beam members




Select small display size for supports





Select small display size for loads



Specification of two vehicle live loads (load-trains)


Highway design load-train (vehicle live load): extension = 8 m

Live load (population of small vehicles):

Exterior: $q_{ext} = 12 \text{ kN/m}$

Interior: $q_{int} = 4 \text{ kN/m}$

Impact coefficient: 1.0




Rail road design load-train: extension = bridge length

Train car loads:

Full car: $q = 12 \text{ kN/m}$


Empty car: $q' = 2 \text{ kN/m}$

Impact coefficient: 1.0






Creation of highway load-train with four axes




Specification of highway load-train length, values of concentrated forces, and values of interior and exterior live loads (population of small vehicles)






Creation of railroad load-train




Specification of railroad load-train length, values of concentrated forces, and values of full and empty car distributed loads






Select result visualization step (2 m) and set transversal display of result values




Select cross-section for visualization of shear force influence line result






Visualization of shear force influence line result and critical positions (that cause minimum and maximum) of highway load-train




Visualization of bending moment influence line result and critical positions (that cause minimum and maximum) of highway load-train






Visualization of axial force influence line result and critical positions (that cause minimum and maximum) of railroad load-train




Visualization of shear force envelopes for highway load-train (including effect of permanent load)






Visualization of bending moment envelopes for railroad load-train (including effect of permanent load)



Visualization of bending moment envelopes for railroad load-train (excluding effect of permanent load)





Consulting step results values along central beam member of bending moment envelopes for railroad load-train (excluding effect of permanent load)

